



IMAGE

FV SERIES TRANSMITTERS



Prototek continues bringing new technology to the locating industry. These FV Series **512 Hz** transmitters are small and durable. They're made of solid brass and the same tough urethane used to line rock tumblers. A gold battery contact prevents corrosion and the rubber O-ring seals out moisture. Attach one to your push rod, behind a camera, jetter or put it in our spring carrier and use with your cable for those tough jobs. Give us a call to order today!



FV-10

- Compatible with all 512 Hz receivers
- Size: 3/4 inch X 3 1/4 inches
- Range: 10 feet thru cast iron, 15 feet through nonmetallic
- Signal tone: Continuous
- Duration: 8 hours
- Power: One Alkaline AAA Battery
- Line size: Moves through lines down to 2 inches



FV-20

- Compatible with all 512 Hz receivers
- Size: 3/4 inch X 3 1/2 inches
- Range: 20 feet thru cast iron, 30 feet through nonmetallic
- Signal tone: Continuous
- Duration: 8 hours
- Power: One Alkaline AAA Battery
- Line size: Moves through lines down to 2 inches



FV-40

- Compatible with all 512 Hz receivers
- Size: 1 3/4 inches X 9 1/2 inches
- Range: 40 feet thru cast iron, 60 feet through nonmetallic
- Signal tone: Continuous
- Duration: 8 hours
- Power: 3 Alkaline C-Cell Batteries
- Line size: Moves through lines down to 4 inches



IMAGE
INSPECTION SERVICES LTD.

Image Inspection Services Ltd.
4650 - 50th Avenue S.E.
Calgary, Alberta
T2B 3R4

Phone: (403) 287-1053
Fax: (403) 243-4564

Toll Free
1-800-667-6670

Email: sales@image-inspect.com
Web: www.image-inspect.com