



### General Description

The gopher crawler is the intermediate member of a family of 3 robust wheeled camera crawlers. Pipe diameters from 6" to 24" pipe are possible with the use of various sizes of solid or pneumatic wheels and spacers. The camera can carry standard or pan and tilt cameras, but does require a front mounted mini camera when negotiating 6" diameter pipe. For 4" pipe see the Mole wheeled crawler, and for 8" and larger or steerable applications see the Wolverine crawler. This crawler is best suited for lines up to 500' in length.

### Features

- Solid anodized aluminum or brass body
- High torque 48 volt motor
- 3 sizes of solid sanitary tire available
- 3 sizes of pneumatic storm tire available
- Adaptable to multi-conductor systems
- Available with desktop or 12" rack mounted controller
- 14" length, 5" width, 5" height
- Stainless steel wheel hubs and axles
- O-ring sealed drive axles and bearings
- Internal all four wheel drive
- Forward, reverse, variable speed
- Up to 500' pulls on mini camera cable
- Perfect mate to our model 2 series of camera control units and hand or cube cable reels with mini camera cable



**IMAGE**  
**INSPECTION SERVICES LTD.**

Image Inspection Services Ltd.  
4650 - 50th Avenue S.E.  
Calgary, Alberta  
T2B 3R4

Phone: (403) 287-1053  
Fax: (403) 243-4564

Toll Free  
1-800-667-6670

Email: [sales@image-inspect.com](mailto:sales@image-inspect.com)  
Web: [www.image-inspect.com](http://www.image-inspect.com)